AMENDMENTS TO THE CLAIMS:

Replace the claims with the following rewritten listing:

1.-15. (Cancelled)

16. (Previously Presented) Foil-type switching element comprising:

a first carrier foil and a second carrier foil arranged at a distance from each other by means of a spacer, said spacer comprising at least one recess defining an active area of the switching element, and

at least two electrodes arranged in the active area of the switching element between said first and second carrier foils in such a way that, in response to a pressure acting on the active area of the switching element, the first and second carrier foils are pressed together against a reaction force of the elastic carrier foils and an electrical contact is established between the at least two electrodes,

wherein at least one of said first and second carrier foils comprises a multi-layered configuration with an inner supporting foil and an outer elastic activation layer, said outer elastic activation layer being deformable in response to pressure acting thereon in such a way that said outer elastic activation layer presents a greater thickness in a central region of said active area than in a peripheral region of said active area, and thereby presses said inner supporting foil towards the other carrier foil in said central region.

- 17. (Previously Presented) Foil-type switching element according to claim 16, wherein a thickness of said activation layer is substantially larger than the distance between the first and second supporting foil.
- 18. (Previously Presented) Foil-type switching element according to claim 16, wherein both said first and said second carrier foils comprise a multi-layered configuration with an inner supporting foil and an outer elastic activation layer for introducing a force acting on the switching element into a central region of said active area of said switching element.

2

- 19. (Previously Presented) Foil-type switching element according to claim 18, wherein a combined thickness of the two activation layers is substantially larger than the distance between the first and second supporting foil.
- 20. (Previously Presented) Foil-type switching element according to claim 16, wherein said outer activation layer is exclusively located in the region of said active area.
- 21. (Previously Presented) Foil-type switching element according to claim 16, wherein said outer activation layer extends substantially over an entire area of the inner supporting foil.
- 22. (Previously Presented) Foil-type switching element according to claim 16, wherein a first electrode is arranged on an inner surface of said first carrier foil and a second electrode is arranged on an inner surface of the second carrier foil in a facing relationship with said first electrode.
- 23. (Previously Presented) Foil-type switching element according to claim 16, wherein a first and a second electrode are arranged side by side on an inner surface of said first carrier foil and wherein a shunt element is arranged on an inner surface of the second carrier foil in facing relationship with said first and second electrodes.
- 24. (Previously Presented) Foil-type switching element according to claim 16, wherein at least one of said first and second electrode is covered by a resistive material.
- 25. (Previously Presented) Foil-type switching element according to claim 23, wherein said shunt element comprises a resistive material.
- 26. (Previously Presented) Foil-type switching element according to claim 16, wherein at least one of said first and second carrier foils further comprises an outer actuator layer, said

actuator layer being arranged on the side of the activation layer, which faces away from the inner supporting foil.

- 27. (Previously Presented) Foil-type switching element according to claim 16, wherein said activation layer comprises a foam material.
- 28. (Previously Presented) Foil-type switching element according to claim 16, wherein said activation layer comprises a silicon gel.
- 29. (Previously Presented) Foil-type switching element according to claim 16, wherein said activation layer comprises a rubber like material.
- 30. (Previously Presented) Foil-type switching element according to claim 16, wherein said activation layer comprises a fluid filled cushion.